

User Interface Demo Board NA/ANZ



Specification Sheet

System Kits > Demonstration



Versatile design, unrivalled functionality

The PD-UI-NA-DemoBoard provides an easily transportable all-in-one showcase of Dynalite button panel UIs and finishes in the rectangular form factor most commonly found in North American, South American, Australian, and New Zealand markets.

Use the board as a basic display, or add communication and power modules for live demonstrations.

Key Features

- **3x Antumbra Touch NA/ANZ** – Capacitive touch control in black, white, and silver.
- **1x Antumbra Display NA/ANZ** – Integrated LCD display provides system information and up to 16 pages of controls.
- **3x Antumbra Button NA/ANZ** – Two/four/six-button variants with various finishes.
- **3x Revolution NA/ANZ** – Two/four/eight-button variants with mix-and-match button and frame finishes and RGB backlighting.
- **DUS360CR multifunction sensor** – 360° motion detection, lux level monitoring, and IR control.
- **Fascia samples** – See and feel our growing range of additional finishes for Antumbra Button and Antumbra Display.
- **Button labelling examples** – All UI buttons are labelled with text and icons created in the online Dynalite Design Studio.
- **Power supply and communication modules sold separately** – Add one DACM per Antumbra/Revolution and a power supply to enable live demonstrations of each device's capabilities.
- **Configuration files available on request** – Our system experts have everything you need to get your live demonstrations up and running with zero hassle. Contact your Dynalite representative for more information.

Specifications

Electrical	
Supply Type	SELV / CLASS 2 (UL) external, regulated DC (sold separately, see Ordering Codes)
Supply Voltage	12-24 VDC
Notes	Refer to individual device specification sheets for electrical requirements.

Included Devices	
User Interfaces	PATPA (Antumbra Touch NA/ANZ) PADPA (Antumbra Display NA/ANZ) PAxBA (Antumbra Button NA/ANZ) PDRxA (Revolution NA/ANZ)
Sensors	DUS360CR

Physical	
Dimensions	530 x 605 x 360 mm (20.80 x 23.80 x 14.20 in)
Packed Dimensions	580 x 630 x 75 mm (22.83 x 24.80 x 2.95 in)
Packed Weight	10 kg (22.05 lb)

Environment	
Operating Temperature	0° to 45°C ambient (32° to 113°F)
Storage/Transport Temperature	-25° to 60°C ambient (-13° to 140°F)
Relative Humidity	≤90% non-condensing
Installation Note	Indoor use only

Ordering Codes

Product	12NC
PD-UI-NA-DemoBoard	913703372409

Accessory		12NC
DDNP1501	Network Power Supply	913703130509
DACM (DyNet)	DyNet communication module	913703072809
DINGUS-DUS-DUAL-RJ12	Dual RJ12 connector - pack of 10	913703064309
DINGUS-UI-DUAL-RJ45	Dual RJ45 connector - pack of 10	913703334609