

PD-232N

RS-232 PC Node

Signify
Dynalite

Specification Sheet

Accessories > Connectivity Accessories




Serial port connection node

The Dynalite PD-232N is a network gateway that provides passive integration to a PC or RS-232 system.

Key Features

- **Full duplex integration** – links the Dynalite system to AV or HVAC systems supporting passive RS-232
- **Versatile mounting** – robust housing with cable tie attachment points for server racks

Dimensions




Specifications

Electrical		Physical	
Supply Type	DyNet	Dimensions	76 x 70 x 24 mm (3.0 x 2.76 x 0.94 in)
Supply Voltage	12-24 VDC	Packed Weight	278 g (0.61 lb)
Supply Current	50 mA	Construction	Polycarbonate
IEC Overvoltage Category	II	Serial Ports	1 x 5-way pluggable screw terminal 1 x DB9 Female
Control		Serial Port Conductor Size	0.3-2.5 mm ² (#22-12 AWG)
Communication Ports	1 x RS-485 1 x RS-232	Environment	
Supported Protocols	DyNet	Operating Temperature	0° to 50°C ambient (32° to 122°F)
Indicators	1 x DyNet Power LED (red) 1 x Data LED (green)	Storage Temperature	-25° to 70°C ambient (-13° to 158°F)
		Relative Humidity	≤90% non-condensing
		IEC Pollution Degree	II
		Installation Note	For indoor installation only
Compliance			
		Certifications	CE, RCM, UKCA, FCC, ISED
		Sustainability	RoHS
		IP Rating	IP20



Electrical Drawing

12-24 V == 50 mA
RS-485 DyNet
SELV / Class 2 (UL)



Ordering Codes

Product	12NC
PD-232N	913703098409

Accessory	12NC
1 x RS-232 Male-to-Female Cable	(Supplied)
1 x 5-pin pluggable screw terminal	(Supplied)