

Specification Sheet

User Interfaces > Revolution




Contemporary touchscreen user interface

Contemporary touchscreen user interface. The Dynalite Revolution Display features a sleek, contemporary design and dynamically detects and responds to user presence. The full-colour capacitive touchscreen display can perform a variety of local and site-wide control functions. The Revolution Euro range is suitable for, but not limited to, European, Middle Eastern, African and Asian markets.

Key Features

- **User proximity detection** – The user interface detects an approaching user and lights up to encourage interaction, then dims automatically as they move away to reduce light pollution.
- **Colour touchscreen display** – Provides at-a-glance system information with intuitive, easily understandable control options.
- **Supplied as two components** – The Application Module contains buttons, rim, base, and mounting plate, which can be mixed and matched to suit décor. The Communication Module contains all of the logical and network functions and is pre-programmed off-site, allowing commissioning to commence prior to finish options being finalised.
- **Multiple language and icon labelling** – Language choices include English, Chinese, and Arabic. A library of common icons transcends language barriers, which is particularly useful in hospitality applications.
- **Hidden sensory inputs** – An internal light sensor measures ambient light and adjusts the lightwash effect accordingly. A built-in temperature sensor automatically adjusts air conditioning when integrated into the system.

Dimensions



Specifications

Electrical	
Supply Type	DyNet
Supply Voltage	12–24 VDC (SELV/Class 2)
Supply Current	120 mA (max) @ 12 VDC 60 mA (max) @ 24 VDC
IEC Overvoltage Category	II

Display	
Display Type	a-Si TFT LCD capacitive touchscreen
Display Resolution	720 x 720 px
Viewable Area	72 x 72 mm (2.83 x 2.83 in)
Colour Depth	16.7 million colours
Viewing Angle	80°

Application Module	
Temperature Sensor Range	5° to 40°C (41° to 104°F)
Temperature Sensor Accuracy	± 1°C (± 1.8°F)
Field Effect Detection Range	approx. 10 cm (4 in)

Communication Module	
Serial Ports	1 x RS-485
Supported Protocols	DyNet
User Controls	1 x service switch
Indicators	1 x service LED

Physical	
Dimensions	88 x 88 x 38 mm (3.46 x 3.46 x 1.5 in) (Fully assembled)
Packed Weight	Application module: 0.2 kg (0.44 lb) Communication module: 0.12 kg (0.25 lb)
Serial Ports	1 x 5-way pluggable screw terminal
Serial Port Conductor Size	0.3–2.5 mm² (#22–12 AWG)

Environment	
Operating Temperature	0° to 50°C ambient (32° to 122°F)
Storage/Transport Temperature	–25° to 70°C ambient (–13° to 158°F)
Relative Humidity	≤90% non-condensing
IEC Pollution Degree	II
Installation Note	Indoor installation only

Compliance	
Certifications	CE, RCM, FCC, UKCA
Sustainability	RoHS
IP Rating	IP40



Ordering Codes

Application Module Ordering Codes

The Application Module contains the display assembly and metal mounting plate that attaches the Revolution panel securely to the wall, ensuring stable, reliable operation.

Product		12NC
PDRDxxE-xxB-x	Black	913703375209
PDRDxxE-xxW-x	White	913703252009

Communication Module

The Dynalite Application Communication Module (DACM v5 or later) is compatible with all interfaces across the Revolution series, and can be ordered, programmed, installed, wired and tested without the Application Module attached.



This allows the commissioning process to begin before the final finish options have been chosen, or during construction, and protects the Application Module from damage until the site is ready for occupancy.

Product		12NC
DACM (DyNet)	DyNet comms module	913703072809

Accessory		12NC
D-DACM-DINGUS-RJ12-QTY10	Dual RJ12 connector with earth wire – pack of 10	913703255209
D-DACM-DINGUS-RJ45-QTY10	Dual RJ45 connector with earth wire – pack of 10	913703254809

Policies and Notices

Specific Data Notice

This Specific Data Notice applies to the User Interfaces as specified in this product specification sheet (the "**User Interface**") that is part of or works with a Professional System offered by Signify for use in the European Union and supplements and/or corrects the Generic Data Notice For Professional Systems and Services that can be found at <https://www.signify.com/global/resources/policies-announcements> (the "**Generic Data Notice**") by providing additional and/or more specific details specific to this User Interface.

Terms starting with a capital in this Specific Data Notice will have the meaning as attributed thereto in the Generic Data Notice, unless explicitly defined otherwise in this document.

When used in a Signify professional lighting system in combination with a Dynalite Gateway with either the Dynalite Switch App, Dynalite System Builder, Dynalite System Manager, or Dynalite Cloud, the User Interface can generate the Data as specified below (The type and volume and format of the Data that is generated depends on the product and/or software configuration and subscription to the relevant software service):

- Operational Data: Lighting control commands based on events configured in this product via the RS-485 DyNet network.
- Sensor Data: Temperature and Humidity reporting via the RS-485 DyNet network

The Data generated in this combination is communicated via the network to the gateway and is stored on the gateway. If configured to do so, the gateway can forward the Data to Dynalite Cloud or to Dynalite System Manager. For applicable retention period and means of access to Data that is Readily Available Data, please refer to the Dynalite Cloud software specification sheet. Data cannot be accessed directly from the User Interface (In typical use, once the connected product has been commissioned, data generated on the device is not directly accessible). Data can be accessed from the Gateway using Dynalite System Builder or directly from any of the APIs of the Gateway. The Gateway will persist the Data for 28 days on a rolling basis.

This Specific Data Notice may be changed by Signify from time to time. The current version of this notice will apply and can be obtained at request via the point of contact as indicated in paragraph 7 of the Generic Data Notice.